



<b>A</b>	Min. afstand tussen de scharnieren in mm	Minimum distance between the hinges in mm	Entraxe minimum entre les charnières en mm	Min. Abstand zwischen den Torbändern in mm
<b>L</b>	Lengte van de poort in mm	Gate length in mm	Longueur du portail en mm	Torlänge in mm
<b>G</b>	Maximum-gewicht van de poort in kilogram (kg)	Maximum gate weight in kilogram (kg)	Poids maximal du portail en kilogrammes (kg)	Maximum-gewicht des Tores in Kilogramm (kg)

## GBMUM16

Max. trekkracht / scharnier	Max. pull power / hinge	Force de traction max./charnière	Max. Zugkraft / Torband	<b>60000 N</b>
Veiligheids-factor	Safety Factor	Facteur de sécurité	Sicherheitsfaktor	<b>6</b>

		<b>L</b>								
		750	1000	1250	1500	2000	2500	3000	3500	4000
<b>A</b>	500	659	464	348	270	173	114	76	48	27
	750	1048	756	581	464	319	231	173	131	100
	1000	1189	1048	814	659	464	348	270	214	173
	1250	1189	1189	1048	853	610	464	367	298	246
	1500	1189	1189	1189	1048	756	581	464	381	319
	1750	1189	1189	1189	1189	902	698	562	464	391
	2000	1189	1189	1189	1189	1048	814	659	548	464
	2500	1189	1189	1189	1189	1189	1048	853	714	610
	3000	1189	1189	1189	1189	1189	1189	1048	881	756
	3500	1189	1189	1189	1189	1189	1189	1189	1048	902
4000	1189	1189	1189	1189	1189	1189	1189	1189	1048	
		<b>G</b>								

## GBMUM18

Max. trekkracht / scharnier	Max. pull power / hinge	Force de traction max./charnière	Max. Zugkraft/ Torband	<b>60000 N</b>
Veiligheids-factor	Safety Factor	Facteur de sécurité	Sicherheits-faktor	<b>6</b>

		L								
		750	1000	1250	1500	2000	2500	3000	3500	4000
A	500	1129	796	596	463	296	196	129	82	46
	750	1796	1296	996	796	546	396	296	225	171
	1000	2039	1796	1396	1129	796	596	463	368	296
	1250	2039	2039	1796	1463	1046	796	629	510	421
	1500	2039	2039	2039	1796	1296	996	796	653	546
	1750	2039	2039	2039	2039	1546	1196	963	796	671
	2000	2039	2039	2039	2039	1796	1396	1129	939	796
	2500	2039	2039	2039	2039	2039	1796	1463	1225	1046
	3000	2039	2039	2039	2039	2039	2039	1796	1510	1296
	3500	2039	2039	2039	2039	2039	2039	2039	1796	1546
4000	2039	2039	2039	2039	2039	2039	2039	2039	1796	
		G								

## GBMUM20

Max. trekkracht / scharnier	Max. pull power / hinge	Force de traction max./charnière	Max. Zugkraft/ Torband	<b>60000 N</b>
Veiligheids-factor	Safety Factor	Facteur de sécurité	Sicherheits-faktor	<b>6</b>

		L								
		750	1000	1250	1500	2000	2500	3000	3500	4000
A	500	1129	796	596	463	296	196	129	82	46
	750	1796	1296	996	796	546	396	296	225	171
	1000	2039	1796	1396	1129	796	596	463	368	296
	1250	2039	2039	1796	1463	1046	796	629	510	421
	1500	2039	2039	2039	1796	1296	996	796	653	546
	1750	2039	2039	2039	2039	1546	1196	963	796	671
	2000	2039	2039	2039	2039	1796	1396	1129	939	796
	2500	2039	2039	2039	2039	2039	1796	1463	1225	1046
	3000	2039	2039	2039	2039	2039	2039	1796	1510	1296
	3500	2039	2039	2039	2039	2039	2039	2039	1796	1546
4000	2039	2039	2039	2039	2039	2039	2039	2039	1796	
		G								

## GBMUM22

Max. trekkraft / scharnier	Max. pull power / hinge	Force de traction max./charnière	Max. Zugkraft / Torband	<b>65000 N</b>
Veiligheids-factor	Safety Factor	Facteur de sécurité	Sicherheits-faktor	<b>6</b>

		<b>L</b>								
		750	1000	1250	1500	2000	2500	3000	3500	4000
<b>A</b>	500	1224	862	646	501	321	212	140	89	50
	750	1946	1404	1079	862	592	429	321	243	185
	1000	2209	1946	1512	1224	862	646	501	398	321
	1250	2209	2209	1946	1585	1133	862	682	553	456
	1500	2209	2209	2209	1946	1404	1079	862	708	592
	1750	2209	2209	2209	2209	1675	1296	1043	862	727
	2000	2209	2209	2209	2209	1946	1512	1224	1017	862
	2500	2209	2209	2209	2209	2209	1946	1585	1327	1133
	3000	2209	2209	2209	2209	2209	2209	1946	1636	1404
	3500	2209	2209	2209	2209	2209	2209	2209	1946	1675
4000	2209	2209	2209	2209	2209	2209	2209	2209	1946	
		<b>G</b>								